3M[™] Peltor[™] Technical Datasheet

3M [™] Peltor [™] Ground Mechanic Adapters

FL5008 GB, FL5008-02 GB

Product desription

The PTT button is logically placed so that it is easy to access with either hand. The design makes it easy to use even with heavy gloves. The PTT button has a specific pressure point. The jack is at a 10 degree angle to the fixed cord and positioned so that the headset is easy to plug in and unplug in all situations.

Key Features:

- Designed to fit the shape of the hand
- Clamp can be twisted 360 degrees
- Oil resistant cable

Applications

Ground Mechanic work

Standards and Approval:

The Product has been shown to meet the requirements of the European Directive 2004/108/EC and is thus CE marked. The product has been verified in accordance with EN61000-6-2:2005.

Size:

PTT house: 80x60x40 mm

Materials and data:

Box: TPE

Model

Cable: Self extinguishing PUR sheeting

Connector and cable:

PTT house connector: 4-pole, TP-120 equivalent

Cable

FL5008 GB	6-cores neon green, 6,5 m	3-pole
FL5008-02 GB	6-cores neon green, 3,0 m	3-pole

Use and storage:


Storage temperature: -20°C to +55°C, humidity <85%

Usage temperature: -20°C to +55°C Maximum recommended shelf life: 5 years

Use limitations:

Never modify or alter this product.





Warranty:

Connector

The warranty does not cover any damage caused by neglected maintenance or careless handling. For more information on maintenance, please see the user instruction. For complete warranty condition, contact your dealer or local 3M office.

Important Notice:

3M does not accept liability of any kind, be it direct or consequential (including, but not limited to, loss of profits, business and/or goodwill) arising from reliance upon any information herein provided by 3M. The user is responsible for determining the suitability of the products for their intended use. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Occupational Health & Environmental Safety Division 3M Svenska AB, Box 2341 SE-331 02 Värnamo Sweden Phone: +46 (0) 370 65 65 65

Fax: +46 (0) 370 65 65 99 Email: peltorcommunications@mmm.com Internet: www.3M.com/Peltorcomms